

# AEG

## LSK Series Contactors - 3Pole



### Contactors Selection & Data

Part Number	Horsepower (AEG)						Amperage	
	Single Phase		Three Phase				Full Load	AC-1 (Resistive)
	115V	230V	208V	230V	460V	575V		
LS4K-310-*	0.75	1.5	3	3	5	<b>7.5</b>	10	25
LS5K-310-*	0.75	2	3	3	7.5	<b>10</b>	13.8	25
LS7K-310-*	1	3	5	5	10	<b>15</b>	17.5	32
LS11K-300-*	1.5	3	5	7.5	15	<b>15</b>	17.5	45
LS12K-310-*	2	3	7.5	7.5	15	<b>20</b>	22	45
LS15K-300-*	2	5	10	10	20	<b>25</b>	32	60
LS18K-300-*	3	5	10	10	25	<b>25</b>	34	60
LS22K-300-*	3	7.5	15	15	30	<b>40</b>	48	90
LS30K-300-*	5	10	20	20	40	<b>50</b>	62	110
LS37K-300-*	5	15	20	25	50	<b>60</b>	68	110
LS45K-300-*	7.5	15	25	30	60	<b>75</b>	80	140
LS55K-300-*	10	20	30	40	75	<b>75</b>	96	140
LS75K-322-*	-	-	40	50	100	<b>125</b>	140	250
LS90K-322-*	-	-	50	60	125	<b>150</b>	156	250
LS110K-322-*	-	-	60	75	150	<b>150</b>	175	315
LS132K-322-*	-	-	60	75	150	<b>150</b>	192	315
LS160K-322-*	-	-	100	100	250	<b>300</b>	302	450
LS220K-322-*	-	-	125	150	300	<b>400</b>	398	600
LS280K-322-*	-	-	150	200	400	<b>500</b>	480	700
LS375K-322-*	-	-	200	250	500	<b>600</b>	602	1000

* - Coil Selection ( LS4K - LS90K )			* - Coil Selection ( LS110K - LS375K )		
AC	DC	Suffix	AC	DC	Suffix
24V	-	G	24-28V	24-28V	GN
120V	-	A	110-127V	110-127V	AP
208/230V	-	C	220-250V	220-250V	CR
347V	-	347V	440-500V	440-500V	EX
480V	-	E			
600V	-	F			
-	12V	MSW			
-	24V	NSW			
-	48V	OSW			
-	110V	PSW			

Contactors Coil Suffix are designated above and left

\* - Ordering Code Example: **LS7K-310-A**

Note: The AEG (LSK Series) contactors are IEC and NEMA rated. Please contact our factory for further information concerning these dual ratings.