





Overload Relays - Class 10  
B18K



Overload Selection and Data

Class 10 Overload Relays	Direct Mount	Manual/Auto Reset	B18K-*	
	Separate Mount	Manual/Auto Reset	B18K-AD-*	
For use with AEG Contactors:		7.5 - 25hp @ 575V (LS4K, LS5K, LS7K, LS11K, LS12K, LS15K, LS18K)		
Type:		3 Pole, Differential (phase unbalanced protection)		
Ambient Temperature:		-25 to +68 degree Celsius		
Auxiliary Contacts:		Two Independent double breaker contacts (B600, Q600)		
Net Weight:		7 oz / 0.2Kg		
Dimensions:		2.52" H x 1.77" W x 4.24" D		
Part Number:	Current Rating: (Adjustable)	Maximum Fuse Rating (Amperes)	Max Circuit Breaker Rating (Amperes)	
B18K-B	0.16 - 0.26A	1	15	
B18K-C	0.25 - 0.41A	1	15	
B18K-D	0.4 - 0.65A	3	15	
B18K-E	0.65 - 1.1A	6	15	
B18K-F	1.0 - 1.5A	6	15	
B18K-G	1.3 - 1.9A	6	15	
B18K-H	1.8 - 2.7A	10	15	
B18K-I	2.5 - 4.0A	15	15	
B18K-K	4.0 - 6.3A	20	15	
B18K-L	5.5 - 8.5A	25	15	
B18K-M	8 - 12A	40	30	
B18K-N	10 - 16A	50	35	
B18K-O	14.5 - 18A	60	40	
B18K-OM	17.5 - 22A	70	50	
B18K-ON	21 - 26A	80	60	
B18K-P	25 - 32A	100	80	
B18K-Q	30 - 40A	100	80	