



3-Pole Contactors (40hp @ 575V)
ECX65



Contactor Selection and Data

		HP @ 575V			
		40hp			
AC Contactors	Full Voltage Non-Reversing	ECX65-*	-	-	
	Reversing	RECX65-*	-	-	
Auxiliary Contacts	Maximum Aux Contacts	6 (2 Built In)	-	-	
	Maximum Contact Blocks	1	-	-	
Auxiliary Contacts Amperage (A600, P600)		10A	-	-	
AC-1 (Resistive) Amperage		80A	-	-	
Full Load Amperage @ 240V (AC-3)		68A	-	-	
Horsepower Ratings	Single Phase	115V	5	-	-
		230V	15	-	-
	Three Phase	200V	20	-	-
		230V	25	-	-
		460V	40	-	-
		575V	40	-	-

* - Coil Selection			Coil Data		
AC	DC	Suffix	-	AC	-
24V	-	G	Inrush Burdon	200VA	-
120V	-	A	Holding Burdon	20VA	-
208/230V	-	C	Pick Up Voltage (+/-)	10+ / -15 %	-
480V	-	E	Drop Out Voltage (-)	(-) 20-75%	-
600V	-	F	Maximum Operations		
			Mechanical Operations	6,000,000	-
			Electrical Operations	600,000	-
Dimensions		Height (Inch)	Width (Inch)	Depth (Inch)	
		5.08"	3.0"	4.6"	