



3-Pole Contactors (50hp @ 575V)  
ECX95



Contactor Selection and Data

		HP @ 575V			
		50hp			
AC Contactors	Full Voltage Non-Reversing	ECX95-*	-	-	-
	Reversing	RECX95-*	-	-	-
Auxiliary Contacts	Maximum Aux Contacts	6 (2 Built In)	-	-	-
	Maximum Contact Blocks	1	-	-	-
Auxiliary Contacts Amperage (A600, P600)		10A	-	-	-
AC-1 (Resistive) Amperage		95A	-	-	-
Full Load Amperage @ 240V (AC-3)		80A	-	-	-
Horsepower Ratings	Single Phase	115V	7.5	-	-
		230V	20	-	-
	Three Phase	200V	30	-	-
		230V	30	-	-
		460V	50	-	-
	575V	50	-	-	

* - Coil Selection			Coil Data		
AC	DC	Suffix	-	AC	-
24V	-	G	Inrush Burdon	200VA	-
120V	-	A	Holding Burdon	20VA	-
208/230V	-	C	Pick Up Voltage ( +/- )	10+ / -15 %	-
480V	-	E	Drop Out Voltage ( - )	(-) 20-75%	-
600V	-	F	Maximum Operations		
			Mechanical Operations	6,000,000	-
			Electrical Operations	600,000	-
Dimensions		Height (Inch)	Width (Inch)	Depth (Inch)	
		5.08"	3.43"	5.0"	