

AEG

LSK Series Contactors - 4Pole



Contactors Selection & Data

Part Number	Horsepower (AEG)						Amperage	
	Single Phase		Three Phase				Full Load	AC-1 (Resistive)
	115V	230V	208V	230V	460V	575V		
LS5K-400-*	0.75	2	3	3	7.5	10	14	25
LS7K-400-*	1	3	5	5	10	15	18	32
LS11K-400-*	1.5	3	5	7.5	15	20	25	45
LS15K-400-*	2	5	10	10	20	25	32	60
LS18K-400-*	3	7.5	10	15	30	30	42	80
LS30K-400-*	5	10	20	20	40	50	62	110
LS45K-400-*	7.5	15	25	30	60	75	80	140
LS55K-400-*	10	20	30	40	75	75	96	140
LS90K-411-*	-	-	50	60	125	125	156	250
LS132K-411-*	-	-	60	75	150	150	192	315
LS160K-411-*	-	-	100	100	250	300	302	450
LS220K-411-*	-	-	125	150	300	400	398	600
LS280K-411-*	-	-	150	200	400	500	480	700
LS375K-411-*	-	-	200	250	500	600	602	1000

2NO/2NC Power Poles

LS5K-R00-*	0.75	2	3	3	7.5	10	14	25
LS7K-R00-*	1	3	5	5	10	15	18	32
LS11K-R00-*	1.5	3	5	7.5	15	20	25	45
LS15K-R00-*	2	5	10	10	20	25	32	60
LS18K-R00-*	3	7.5	10	15	30	30	42	80
LS30K-R00-*	5	10	20	20	40	50	62	110
LS37K-R00-*	5	15	20	25	50	60	68	110

* - Coil Selection (LS4K - LS90K)			* - Coil Selection (LS132K - LS375K)		
AC	DC	Suffix	AC	DC	Suffix
24V	-	G	24-28V	24-28V	GN
120V	-	A	110-127V	110-127V	AP
208/230V	-	C	220-250V	220-250V	CR
347V	-	347V	440-500V	440-500V	EX
480V	-	E			
600V	-	F			
-	12V	MSW			
-	24V	NSW			
-	48V	OSW			
-	110V	PSW			

Contactors Coil Suffix are designated above and left

* - Ordering Code Example: **LS7K-400-A**

Note: The AEG (LSK Series) contactors are IEC and NEMA rated. Please contact our factory for further information concerning these dual ratings.

